


Welded
Mesh

WELDED MESH

Mesh width 25x25

Mat sizes with plus tolerances, wire projections on all sides.

Information on galvanised welded meshes: the zinc coating of the pregalvanised wires is 25-40 my (significantly less at the crossing points). The protective edges at the wire ends remain unprocessed. Corrosion protection (limited) present without further processing. From a visual and technical point of view, an optimal surface, e.g. with regard to subsequent plastic coating or painting. You can find the suitable profile edgings on page 349 onwards.




Material	Mesh width l x b in mm	Thickness s in mm	Dimensions in mm	For Profiles of Slit Breadth in mm	Item number	Weight in kg/m ²
galvanized steel	25x25	3.0	1000 x 2000	3.00	101214	4.4

WELDED MESH

Mesh width 30x30

Mat sizes with plus tolerances, wire projections on all sides.

Information on galvanised welded meshes: the zinc coating of the pregalvanised wires is 25-40 μm (significantly less at the crossing points). The protective edges at the wire ends remain unprocessed. Corrosion protection (limited) present without further processing. From a visual and technical point of view, an optimal surface, e.g. with regard to subsequent plastic coating or painting. You can find the suitable profile edgings on page 349 onwards.




Material	Mesh width l x b in mm	Thickness s in mm	Dimensions in mm	For Profiles of Slit Breadth in mm	Item number	Weight in kg/m ²
steel						
	30x30	3.0	1000 x 2000	3.00	101360	3.6
	30x30	3.0	1250 x 2500	3.00	100755	3.6
	30x30	3.0	1500 x 3000	3.00	101361	3.6
galvanized steel						
	30x30	3.0	1000 x 2000	3.00	101406	3.6
	30x30	3.0	1500 x 3000	3.00	101407	3.6
stainless steel						
X5CrNi18-10 2B	30x30	3.0	1000 x 2000	3.00	100763	3.6
	30x30	3.0	1250 x 2500	3.00	101221	3.6

WELDED MESH

Mesh width 40x40

Mat sizes with plus tolerances, wire projections on all sides.

Information on galvanised welded meshes: the zinc coating of the pregalvanised wires is 25-40 my (significantly less at the crossing points). The protective edges at the wire ends remain unprocessed. Corrosion protection (limited) present without further processing. From a visual and technical point of view, an optimal surface, e.g. with regard to subsequent plastic coating or painting. You can find the suitable profile edgings on page 349 onwards.



Material	Mesh width l x b in mm	Thickness s in mm	Dimensions in mm	For Profiles of Slit Breadth in mm	Item number	Weight in kg/m ²
steel						
	40x40	4.0	1000 x 2000	4.00	100756	4.9
	40x40	4.0	2000 x 3000	4.00	100757	4.9
galvanized steel						
	40x40	3.0	1000 x 2000	3.00	101215	2.7
	40x40	4.0	2000 x 3000	4.00	101409	4.9
stainless steel						
X5CrNi18-10 2B	40x40	4.0	1000 x 2000	4.00	100764	4.9
	40x40	4.0	1250 x 2500	4.00	101222	4.9




WELDED MESH

Mesh width 50x50

Mat sizes with plus tolerances, wire projections on all sides.

Information on galvanised welded meshes: the zinc coating of the pregalvanised wires is 25-40 μm (significantly less at the crossing points). The protective edges at the wire ends remain unprocessed. Corrosion protection (limited) present without further processing. From a visual and technical point of view, an optimal surface, e.g. with regard to subsequent plastic coating or painting. You can find the suitable profile edgings on page 349 onwards.




Material	Mesh width l x b in mm	Thickness s in mm	Dimensions in mm	For Profiles of Slit Breadth in mm	Item number	Weight in kg/m ²
steel						
	50x50	4.0	1000 x 2000	4.00	100758	4.0
	50x50	4.0	2000 x 3000	4.00	100759	4.0
	50x50	5.0	2000 x 3000	5.00	100760	6.0
galvanized steel						
	50x50	4.0	1000 x 2000	4.00	101216	4.0
	50x50	4.0	2000 x 3000	4.00	101410	4.0
stainless steel						
X5CrNi18-10 2B	50x50	5.0	1000 x 2000	5.00	100765	6.0

WELDED MESH

Mesh width 50x100

Mat sizes with plus tolerances, wire projections on all sides.

Information on galvanised welded meshes: the zinc coating of the pregalvanised wires is 25-40 my (significantly less at the crossing points). The protective edges at the wire ends remain unprocessed. Corrosion protection (limited) present without further processing. From a visual and technical point of view, an optimal surface, e.g. with regard to subsequent plastic coating or painting. You can find the suitable profile edgings on page 349 onwards.




Material	Mesh width l x b in mm	Thickness s in mm	Dimensions in mm	For Profiles of Slit Breadth in mm	Item number	Weight in kg/m ²
steel	50x100	5.0	1250 x 2500	5.00	100761	4.6
galvanized steel	50x100	4.0	1250 x 2500	4.00	101217	3.0
stainless steel X5CrNi18-10 2B	100x50	5.0	1000 x 2000	5.00	101219	4.6

WELDED MESH

Mesh width 100x100

Mat sizes with plus tolerances, wire projections on all sides.

Information on galvanised welded meshes: the zinc coating of the pregalvanised wires is 25-40 my (significantly less at the crossing points). The protective edges at the wire ends remain unprocessed. Corrosion protection (limited) present without further processing. From a visual and technical point of view, an optimal surface, e.g. with regard to subsequent plastic coating or painting. You can find the suitable profile edgings on page 349 onwards.



Material	Mesh width l x b in mm	Thickness s in mm	Dimensions in mm	For Profiles of Slit Breadth in mm	Item number	Weight in kg/m ²
steel	100x100	5.0	2000 x 3000	5.00	100762	3.1
galvanized steel	100x100	4.0	1250 x 2500	4.00	101218	2.0
stainless steel X5CrNi18-10 2B	100x100	5.0	1000 x 2000	5.00	101220	3.1